

Application Data Sheet for A.C. and D.C. Hydraulic Power Packs

Project Number: Engineer Contact: Company (Customer): Customer Company (Customer): Customer Address: Title: PO Box / Suite #: Email: PO Box / Suite #: Email: City: Phone: State: Zip Code: Fax: Phone: Description of Hydraulics Components (Circuit Diagram Required. Send as a separate attachment.) Fit/Form/Function: Exact Source Problems: Target Price: Source Problems: Target Price: Performance Requirements Motor Specifications Ac/Dc-Voltage: RPM: Ac/Did Vpel/Viscosity: D/A Operating Pressure: Anps Max: Duty Cycle: Time On- Time On- Time Off- Phase: Single Stat Under Load: Yes No Type: Field Type/Viscosity: HZ Phase: Single Stat Under Load: Yes Stat Switch: Yes Stat Switch: Yes Valve Solenoid Coil Con	Date:	Bucher Sales /	
Address:	Project Number:		
Address: Contact: Image: Contact	Company (Customer):	Customer	
PO Box / Suite #: Email: Email: Phone: City: Phone: Phone: Phone: State: Zip Code: Fax: Fax: Application Description Fax: Phone: Phone: Description of Hydraulics Components (Circuit Diagram Required. Send as a separate attachment.) Fil/Form/Function: Exact Similar Present Source: Target Price: Poly Steel AC/DC-Voltage: RPM: Phone: Operating Pressure: Poly Steel AC/DC-Voltage: RPM: Phone: Pho			
City:	Address:	Title:	
State: Zip Code: Fax: Application Description	PO Box / Suite #:	Email:	
Application Description Description of Hydraulics Components (Circuit Diagram Required. Send as a separate attachment.) Fit/Form/Function: Exact Source Problems: Target Price: Source Problems: Target Price: Performance Requirements Motor Specifications Ank Size (usable volume): Poly Cylinder Data: D/A Plow Requirement: Min. Operating Pressure: CE Puty Cycle: Time On- Time On- Time Off- Power: KW Plow Control Setting: Phase: Single 3 Itfe Expectancy in Cycles: Frequency: Flow Control Setting: Phase: Start Under Load: Yes Valve Solenoid Coil Connector Type: Comments: Control Switch: Yes Valve Solenoid Coil Connector Type: Envelope Size: Ortertation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Size: Port Type: Comments: Port Size: Comments: Port Size: Port Size: Port Type:	City:	Phone:	
Description of Hydraulics Components (Circuit Diagram Required. Send as a separate attachment.) Fit/Form/Function: Exact Similar Present Source: Yearly Usage:	State: Zip Code:	Fax:	
Fit/Form/Function: Exact Similar Present Source: Yearly Usage:	Application Description		
Present Source: Yearly Usage: Source Problems: Target Price: Source Problems: Target Price: Performance Requirements Motor Specifications Tank Size (usable volume): D/A Source Problems: D/A Source Problems: Motor Specifications Cylinder Data: D/A Source Pressure: Ac/DC-Voltage: Relief Valve Setting: In Puty Cycle: Time On- Time On- Time Off- Power: KW Phase: Single Single 3 Iffe Expectancy in Cycles: Frequency: Flow Control Setting: Thermally Protected: Start Under Load: Yes Start Switch: Yes Start Switch: Yes Valve Solenoid Coil Connector Type: Comments: Control Switch: Yes Valve Solenoid Coil Connector Type: Enclosure: Valve Solenoid Coil Connector Type: Comments: Comments: Yes Port Size: Port Type: Horizontal Vert	Description of Hydraulics Components (Circuit Diagram Required. Send as a separate attachment.)		
Source Problems: Target Price: Performance Requirements Motor Specifications Tank Size (usable volume): Poly Cylinder Data: D/A Source Problems: AC/DC-Voltage: RPM: Amps Max: Flow Requirement: Min. Operating Pressure: C E Duty Cycle: Time On- Time On- Time Off- Power: KW Pluid Type/Viscosity: Phase: Flow Control Setting: Single Control Setting: Thermally Protected: Prequency: TERV Terminal: Yes No Type: Comments: Other: Comments: Comments: Control Switch: Yes Valve Solenoid Coil Connector Type: Envelope Size: Control Switch: Yes Valve Solenoid Coil Connector Type: Envelope Size: Comments: Yes Horizontal Vertical or Variable: Horizontal Vertical or Variable: Comments: Comments: Comments:	Fit/Form/Function: 🗌 Exact 🗌 Similar		
Performance Requirements Motor Specifications Tank Size (usable volume): Poly Steel Cylinder Data: D/A S/A Flow Requirement: Min. / Max. C Terminal: Single Double Operating Pressure: C E UL CSA Duty Cycle: Time On- Time Off- Power: KW HP Pluid Type/Viscosity: Phase: Single 3 Single 3 Iffe Expectancy in Cycles: Time Off- Phase: Single 3 Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Comments: Other: W H Valve Solenoid Coil Connector Type: Envelope Size: L W H Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Type: Port Type: Horizontal Vertical or Variable: Comments: Comments: Comments: Comments:	Present Source:	Yearly Usage:	
Tank Size (usable volume): Poly Stel AC/DC-Voltage: RPM: RPM: Cylinder Data: D/A S/A Amps Max: Double Flow Requirement: Min. / Max. DC Terminal: Single Double Operating Pressure: CE UL CSA ETL Relief Valve Setting: IP Rating: Power: KW HP Pluid Type/Viscosity: Power: KW HP Flow Control Setting: Frequency: HZ Thormally Protected: Yes No Start Under Load: Yes No Electrical Specifications Comments: Comments: Start Switch: Yes No Envelope Size: L W Valve Solenoid Coil Connector Type: Mounting Requirements Port Type: Port Type: Port Size: Port Type: Port Type: Port Type: Comments: Comments: Comments: Comments: Comments: Comments: Port Type: Horizontal Vertical or Variable: Comments: Port Type: Port Type:	Source Problems:	Target Price:	
Cylinder Data: D/A S/A Flow Requirement: Min. / Max. Coperating Pressure: C C UL CSA Relief Valve Setting: C C UL CSA ETL Relief Valve Setting: IP Rating: Power: KW HP Pluid Type/Viscosity: Power: KW HP Flow Control Setting: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Comments: Comments: Comments: Start Switch: Yes No Yalve Solenoid Coil Connector Type: No Length: Yes No Port Size: Port Type: No Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Type: Port Type: Horizontal Uvertical or Variable: Comments:	Performance Requirements	Motor Specifications	
Flow Requirement: Min. / Max. DC Terminal: Single Double Operating Pressure: CE UL CSA ETL Relief Valve Setting: IP Rating: Power: KW HP Duty Cycle: Time On- Time Off- Power: KW HP Fluid Type/Viscosity: Phase: Single 3 Life Expectancy in Cycles: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Comments: Comments: Mounting Requirements Envelope Size: L W H Valve Solenoid Coil Connector Type: No Length: Horizontal Vertical or Variable: Comments: Port Size: Port Type: Horizontal Vertical or Variable: Comments: Comments: <td>Tank Size (usable volume):</td> <td>eel AC/DC-Voltage: RPM:</td>	Tank Size (usable volume):	eel AC/DC-Voltage: RPM:	
Operating Pressure: CE UL CSA ETL Relief Valve Setting: IP Rating: Power: KW HP Fluid Type/Viscosity: Phase: Single 3 Life Expectancy in Cycles: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Other: Comments: Start Switch: Yes No Control Switch: Yes No Length: Mounting Requirements Envelope Size: I W H Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Yes No Port Size: Port Type: Horizontal Vertical or Variable: Comments: Comments: Comments: Comments: Comments: Comments: Comments: No	Cylinder Data: D/A S/A	Amps Max:	
Relief Valve Setting: IP Rating: Duty Cycle: Time On- Time On- Time Off- Power: KW Fluid Type/Viscosity: Phase: Single 3 Life Expectancy in Cycles: Frequency: Flow Control Setting: Thermally Protected: Flow Control Setting: Yes Start Under Load: Yes Electrical Specifications Comments: Start Switch: Yes Yes No Control Switch: Yes Valve Solenoid Coil Connector Type: Envelope Size: Enclosure: Yes No Port Size: Port Type: Horizontal Under Load: Vertical or Variable: Comments: Comments:	Flow Requirement: Min. / M	ax. DC Terminal:	
Duty Cycle: Time On- Time Off- Power: KW HP Fluid Type/Viscosity: Phase: Single 3 Life Expectancy in Cycles: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Other: Other: Other: Other: Other: W H Start Switch: Yes No Length: Mounting Requirements Envelope Size: L W H Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Type: Port Size: Port Type: Horizontal Vertical or Variable: Image: Comments: Comments: Comments: Comments: Image:	Operating Pressure:	CE UL CSA ETL	
Fluid Type/Viscosity: Phase: Single 3 Life Expectancy in Cycles: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Other: Other: Comments: Comments: Valve Solenoid Coil Connector Type: Mounting Requirements Valve Solenoid Coil Connector Type: Enclosure: Yes No Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Type: Port Size: Port Type: Comments: Comments: Comments: Comments: Comments: Comments: Comments: Orient Size: Port Type: Comments: Comments: Comments: Comments: Comments: Comments: Comments: Comments: Comments:	Relief Valve Setting:	IP Rating:	
Life Expectancy in Cycles: Frequency: HZ Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Other: Other: Other: Image:	Duty Cycle: Time On- Time Off-	Power: 🗆 KW 🗆 HP	
Flow Control Setting: Thermally Protected: Yes No Start Under Load: Yes No Type: TENV TEFC Environment/Ambient Temp Range: Other: Other: Other: Electrical Specifications Comments: Other: Other: Start Switch: Yes No Length: Mounting Requirements Control Switch: Yes No Length: Henclosure: Valve Solenoid Coil Connector Type: Envelope Size: L W Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Type: Horizontal Vertical or Variable: Comments:	Fluid Type/Viscosity:	Phase: 🗌 Single 🗌 3	
Start Under Load: Yes No Environment/Ambient Temp Range: Other: Electrical Specifications Start Switch: Yes Ontrol Switch: Yes No Length: Mounting Requirements Envelope Size: L W Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Size: Port Type: Horizontal Overtical or Variable: Comments: Comments: Comments:	Life Expectancy in Cycles:	Frequency: HZ	
Environment/Ambient Temp Range: Electrical Specifications Start Switch: Yes No Control Switch: Yes No Length: Mounting Requirements Envelope Size: L W H Orientation-Motor Terminals, Start Switch, Valve Coils: Port Size: Port Size: Port Size: Port Size: Port Size: Port Type: Horizontal Vertical or Variable: Comments:	Flow Control Setting:	Thermally Protected: Yes No	
Electrical Specifications Comments: Start Switch: Yes Ontrol Switch: Yes Valve Solenoid Coil Connector Type: Mounting Requirements Envelope Size: L Witch: Yes Valve Solenoid Coil Connector Type: Envelope Size: Port Size: Port Type: Hencizontal Vertical or Variable: Comments: Comments:	Start Under Load: 🗌 Yes 🗌 No	Type: 🗌 TENV 🗌 TEFC	
Electrical Specifications Comments: Start Switch: Yes Ontrol Switch: Yes Valve Solenoid Coil Connector Type: Mounting Requirements Envelope Size: L Witch: Yes Orientation-Motor Terminals, Start Switch, Valve Coils: Enclosure: Port Size: Port Type: Horizontal Vertical or Variable: Comments: Comments:	Environment/Ambient Temp Range:	Other:	
Start Switch: Yes Ontrol Switch: Yes No Length: Mounting Requirements Envelope Size: L W H Enclosure: Yes No Port Size: Port Type: Horizontal Overtical or Variable: Comments:		Comments:	
Valve Solenoid Coil Connector Type: Envelope Size: L W H Orientation-Motor Terminals, Start Switch, Valve Coils: Enclosure: Yes No Port Size: Port Type: Horizontal Overtical or Variable: Image: Comments: Comments:			
Orientation-Motor Terminals, Start Switch, Valve Coils: Enclosure: Yes No Port Size: Port Type: Horizontal Vertical or Variable: Comments: Comments:	Control Switch: 🗌 Yes 🗌 No Length:	Mounting Requirements	
Port Size: Port Type: Horizontal Vertical or Variable: Comments: Comments:	Valve Solenoid Coil Connector Type:	Envelope Size:	
Horizontal Vertical or Variable: Comments:	Orientation-Motor Terminals, Start Switch, Valve Coils:	Enclosure: 🗌 Yes 🗌 No	
Comments:		Port Size: Port Type:	
		Horizontal Vertical or Variable:	
		Comments:	
Scheduling			
	Scheduling		
Quote Due Date: - - Quote Approval Required: Yes No	Quote Due Date:	Quote Approval Required: 🗌 Yes 🗌 No	
Quote Drawing Required: Yes No Prototype Required: Yes Qty: No	Quote Drawing Required: 🗌 Yes 🗌 No	Prototype Required: Yes Qty: No	
PPAP Required: Yes No 3D File Required: Yes No Comments:	PPAP Required: Yes No 3D File Required: Yes No	Comments:	

Bucher Hydraulics, Inc.

Tel: +1 (616) 458-1306 • Fax: +1 (616) 458-0079 info.mi@bucherhydraulics.com • www.bucherhydraulics.com