

END VIEW

3.5 Model M-4313 (Formerly M-413)

Description Schematic OUTLET PORT 3/8 NPTF • Pump / Motor / Reservoir / Unit · Manually Operated 2-Way/2-Position Normally Closed Valve · Externally Adjustable Relief Valve · .375 Inch NPT Outlet and Return · Horizontal Mounting Standard • Vertical Mounting / Motor Up Outlet 3-5/8" (92 mm) Relief Valve 11-5/8" (295 mm) 8-1¹/16" (221 mm) 8-1/8" 7-1/2" (206 mm) (191 mm) 1-3/8" (35 mm) 9" (229 mm) 1-5/8" 6-13/16" (173 mm) 1" (25 mm) (41 mm) 24-1/2" (622 mm) 8-1/8" (206 mm)-

Dimensions will vary according to motor output and manufacturer

SIDE VIEW

How to Order Your M-4313 Power System

Comprehensive information may be found on the page referenced below each selection category.

Pump	Motor	Adapter	Reservoir (Length)	Mounting Position	Accessories
Ref. Page 9	Ref. Page 10	Ref. Page 11	Ref. Page 13		Ref. Page 20

500-P-000002-EN-01/09.2015 **29/57**

[&]quot;L" dimension shown for 08751 motor is 10-11/16" (271 mm)

[&]quot;A" dimension for standard 01605 adapter is 2-5/32" (55 mm)

[&]quot;A" dimension for optional 01615 adapter is 3-11/32" (85 mm)